

250L ENVIROSUN ALL IN ONE



FEATURES



Smart
Vacation



Eco Power



Smart
Boost



High
Efficiency



Frost Proof



Anti Freeze



Overheat
Proof



Legionella
Proof

5 years labour warranty and
5 years product warranty

SPECIFICATIONS

MODEL	250EH1-15
Nominal tank volume (L)	250L
Power supply (V/Hz/Phase)	220-40/50/1
Insulation protection	IPX4
Relief valve pressure (kPa)	700
Tank material	Vitreous enamel coated steel
Plumbing connection size	G3/4" F
Corrosion protection	Sacrificial anode
Average heat pump input power (W)	495
Max. heat pump input power (W)	865
Auxiliary heating input power (W)	1500
Max. input power/current (W/A)	2365/9.85
Refrigerant (type/quantity)	R134a/0.9kg
Default temp. setting (OC)	55
Temperature setting range (OC)	35 - 75
Minimum ambient temperature (OC)	-7
Noise level (dBA)	46
Unit weight (net/gross - kg)	102/115
Product dimensions (D*W*H mm)	600*629*1965
Packing dimensions (D*W*H mm)	735*695*2250



(02) 7250 7335

13/168-180 Victoria Road, Marrickville 2204 NSW

www.glower.com.au

