## **300L SMART LIFESTYLE ALL IN ONE**



## **FEATURES**



Wide Operating Range



**Auto Disinfection** 



Low Operating Noise



Tank-Wrapped Condenser Coil



**Power Outage Memory** 



Built in Frost Protection

2 years labour warranty and 5 years product warranty

## **SPECIFICATIONS**

MODEL NO.	SLA-R25-300D/N3D4
Power supply	220-240V~, 1Ph, 50Hz
Nominal tank volume	300 L
Heating capacity (Heat pump only)	2.5 kW
Electic backup heater	2.0 kW
Input (Heat pump only)	610 W
СОР	4.10
Current (Heat pump only)	2.54 A
Max. leaving water temperature	60°C
Hot water yield	52 L/h
Working ambient temperature	-7°C to 40°C
Sound pressure level	48 dB(A)
Water resistance	IPx4
Refrigerant type	R134a
Throttling type	Electric expansion valve
Low pressure protection	yes
High pressure protection	yes
Inner tank	Enamel
Inlet water pipe connection	G3/4" mm
Outlet water pipe connection	G3/4" mm
Condensing water connection	1/2" mm, internal thread
Unit dimension (DxH)	640 x 2,010 mm
Packing dimension (LxWxH)	750 x 745 x 2,210 mm
Net / Gross weight	130 / 144 kg











