

PYTES SOLAR BATTERY



FEATURES

-  IP55-rated enclosure: waterproof and dustproof.
-  Real-time monitoring through the Smart Monitor from Pytes.
-  Unmatched combination of safety, simplicity, and scalability.
-  Compact, stackable design for space efficiency.

10-year warranty

SPECIFICATIONS

MODEL	3	4	5	6
Cell Type	LFP			
Nominal Voltage	51.2V			
Voltage Range	1-6 47.5V~56.8V			
Nominal Capacity	300Ah	400Ah	500Ah	600Ah
Nominal Energy	15.36kWh	20.48kWh	25.6 kWh	30.72kWh
Recommended Power	7.68kW	10.24kW	10.24kW	10.24kW
Dimensions (L*W*H)(inch/mm)	26.8x9.5x41.7 /681x242x1060	26.8x9.5x52.0 /681x242x1320	26.8x9.5x62.2 /681x242x1580	26.8x9.5x72.4 /681x242x1840
Weight (lbs/kg)	393.1/178.3	510.6/231.6	628.1/284.9	745.6/338.2
Efficiency	≥95%			
Communication	CAN, RS485, WIFI, Dry Contact			
WiFi Module	Wifi frequency range:2412-2472MHz Wifi Max. transmission power<20dBm Bluetooth frequency range: 2402-2480MHz Bluetooth Max. transmission power<4dBm			



SPECIFICATIONS

MODEL	3	4	5	6
Operating Temperature	Charge: 32°F~113°F/0°C~45° CDischarge: 14°F~122°F/-10°C~50°C			
Ingress Protection	IP55			
Cycle Life	≥6000 cycles			
Altitude	<13123.35ft/4000m			
Warranty	10 Years			
Certifications	UL9540 Ed3(2023),UL 9540A UL 1973,CE, SGIP			



SAVE BIG ON SOLAR BATTERY INSTALLATION! ✨

With the new government rebate officially live, it's never been more affordable... or more worth it.



GLOWER

(03) 9007 7878

www.glower.com.au

