

HISENSE DUCTED SYSTEM

FEATURES



Control up to 8 zones



Compact design



Easy installation



Inverter technology

Allows the compressor to automatically adjust its speed in response to changes in room temperature and user settings.



5 year warranty

SPECIFICATIONS

ZONE WIRED CONTROLLER MODEL NO.

HACZ01

Dimension (WxH)

120mm x 120mm

Screen Size

4.3 inch

Applicable unit type

Duct

Power supply

DC 12V

Zone quantity

8 zone



ZONE CONTROL INTERFACE MODEL NO.

HAAZ01

Zone quantity

8 zone

Damper power supply

AC 24V

- Zone status control
- Airflow volume control
- HI-NANO

Clean air whenever you need it.



SPECIFICATIONS

INDOOR UNIT MODEL			AUD -140UX4RSH1	AUD -160UX4RSH1
OUTDOOR UNIT MODEL			AUW-140U4RH1	AUW-160U4RH1
Rated capacity	Cooling	kW	14.5	16
	Heating	kW	17.0	18.9
Capacity range	Cooling	kW	6.0~18.5	6.0~18.5
	Heating	kW	6.0~19.5	6.0~20.0
Power input	Cooling	kW	4.09	4.78
	Heating	kW	4.25	4.87
EER/AEER	Cooling	kW/kW	3.55 / 3.52	3.35 / 3.33
COP/ACOP	Heating	kW/kW	4.00/3.968	3.88/3.85
TCSPF (residential)	Cold/average/hot		4.74/4.56/4.89	4.58/4.38/4.69
HSPF (residential)	Cold/average/hot		3.65/4.21/4.70	3.42/4.04/4.67
Airflow (H/M/L)		L/s	1020/810/710	1120/920/780
External static pressure		pa	250	250
Indoor sound level (H/M/L)	Sound pressure	dBA@1.5m	56/53/49	58/55/51
Indoor dimension (HxWxD) (with PCB)		mm	360x1520x820	360x1520x820
Indoor packing dimension (HxWxD)		mm	440x1650x1055	440x1650x1055
Supply air opening flange (HxW)		mm	245x1152	245x1152
Return air opening		mm	2*400(oval)	2*400(oval)
Indoor net weight		kg	66.0	66.0
Outdoor dimension (HxWxD)		mm	1460x975x330	1460x975x330
Outdoor packing dimension (HxWxD)		mm	1590x1040x435	1590x1040x435
Outdoor net weight		kg	98.0	98.0
Power supply		V/Hz	1 phase 220-240V,50Hz	1 phase 220-240V,50Hz
Current	Cooling	A	18.3	21.2
	Heating	A	19.0	21.6
Maximum current (Rated current)		A	31.0	31.0
Liquid pipe diameter		mm	9.5(3/8) (flared)	9.5(3/8) (flared)
Gas pipe diameter		mm	15.9(5/8) (flared)	15.9(3/8) (flared)
Drain		mm	ID 25/OD 32	ID 25/OD 32
Max pipe length		m	75*	75*
Max height drop		m	30	30
Pre charge length		m	30	30
Cooling temperature		°C	-10~50	-10~50
Heating temperature		°C	-15~24	-15~24
Outdoor sound level (H)	Sound power	dBA	77	77
	Sound pressure	dBA@1m	62	62
Gas			R32	R32

 4.8 ★★★★★ 740+ Reviews

GLOWER

 (03) 9007 7878

 www.glower.com.au

